



AL Series Locks & latches





Fire Rated: Tested on fire door assemblies in accordance with Australian Standards, refer fire door manufacturer for specific approval details

The AL Series keyed lever lock utilises the Schlage original A Series cylindrical chassis with a lever design supported by heavy duty spring cages. This design provides strength and performance in more abusive commercial applications.

The AL Series is available in a variety of keyed and non-keyed functions. This series is ideally suited for commercial exterior and interior doors for medical, office, hotel/motel, public and community buildings, retail/store front and government facilities.

Features

- Key removable outside lever for quick re keying and easy cylinder replacement and keying
- Cold rolled steel, machined, threaded hubs and locking nuts prevent loosening of the lockset by bolting chassis to the door
- True through-bolting of door prevents lock chassis rotation and disengagement from latch
- Stainless steel interlocking spindle design for added strength against excess force when lever is in locked position or latch has been fully retracted
- Heavy duty cast mounting plate with specially tapped holes reduces loosening of through-bolting and lockset on the door
- Heavy duty compression springs extend the life of the spring cage and minimises lever droop
- Patented door range adjuster allows quick and easy adjustment of the AL series for 35mm to 48mm thick doors
- Tested in excess of 400,000 operating cycles
- The 10 year warranty provides specifiers and users with assured quality and performance





Specification guide

Function Lever Finish	
Passage latch	ome plateSCP

1.	Function Select the desired function e.g. Entrance lock
2.	Lever Select the desired lever e.g. Neptune
3.	Finish Select the desired finish e.g. Satin chrome plate

Neptune






Specifications

Door type	Timber or metal
Door thickness	35mm to 48mm
Chassis	Cold rolled steel, dichromated plated for corrosion resistance
Lever	Pressure cast zinc
Forend	Stainless steel
Bolt	Brass
Strike plate	Steel
Backsets	70mm latch standard, 60mm, 95mm and 127mm backset available
Key cylinder	Brass plug and cylinder housing, Schlage C6 pin keyway standard, Schlage E6 pin keyway optional, Schlage Everest D keyway optional
Finish	Satin chrome plate
Warranty	10 year mechanical

Door preparation





Schlage AL Series non-keyed

Function Outside Inside

AL10S - Passage latch

Both levers always unlocked



AL25D - Exit lock

Blank plate outside Inside lever always unlocked



AL40S - Bath/bedroom privacy lock

Push-button locking locks outside Levers Turning inside lever or closing door releases button Outside lever has emergency release



AL170 - Single dummy trim

Dummy trim for one side of door Used for door pull or as matching inactive trim



Schlage AL Series keyed

Function Description Outside Inside

AL50PD - Entrance/office lock

Push-button locking: pushing button locks outside lever until unlocked by key or by turning inside lever



AL70PD - Classroom lock

Outside lever locked and unlocked by key Inside lever always unlocked



AL80PD - Storeroom lock

Outside lever fixed Entrance by key only Inside lever always unlocked






Schlage AL Series accessories


Springlatch

Backset: 60mm, 70mm, 95mm and 127mm **Finish:** Satin chrome plate




Deadlatch

Backset: 60mm, 70mm, 95mm and 127mm Finish: Satin chrome plate




Latch front adapter

Black plastic insert used to convert 25mm latch faceplates for 29mm wide door preparations



Rebate kit

This kit adapts latches and strikes for 13mm rebated door and frame preparations



Strikes

Optional lip lengths available **Finish:** Satin chrome plate

